

NAMAQUASTONE MODULAR



PRODUCT RANGE
CLASSIFICATION

CLAY PAVING BRICK
PB - PAVING CLASS B

Clay pavers that are selected or produced for their durability and for their uniformity in size and shape.




Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

NAMAQUASTONE MODULAR



SPECIFICATIONS

Size (length x width x thickness)	220 x 108.5 x 50mm	Average Mass Per Paver	2.6kg
Nibbed	☒ If ticked, yes	Pavers Per Pallet	500
Chamfered	☐ If ticked, yes	Typical 24 Hour Water Absorption	>6%
Factory Manufactured At	Springs, Gauteng	Exposure Zone Suitability	1-3
Pavers per m² (Excl cutting & waste)	41	Traffic	Light Traffic
SANS	-	Dish Drain Channel	☐ If ticked, yes
ISO	9001:2015	Kerb End	☐ If ticked, yes
Average Compressive Strength	>52MPa	Bullnose on Flat	☐ If ticked, yes
Average Modulus of Rupture	>5MPa	Moisture Expansion Category	Category II



www.corobrik.co.za



Combination of Namaquastone and Burgundy Modular pavers

Download the high-resolution swatches, BIM files and view more project photos | www.corobrik.co.za

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.